

Location Information

Full Address : *Near* 21+40 Hwy (24 km NE), Hillsdale, SK ,
 LSD : 101/10-27-042-25w3/00
 NTS :
 Latitude : 49.507487

Main Coordinate System : LSD
 UTM : 12U 600551E 5834132N
 UWI :
 Longitude : -108.542392

Key Information

Rig Type : TDS 3000
 Depth Rating : 3000

Category : TDS 3000
 Racking Capacity :

Drawworks

Mechanical / Electrical : Mechanical
 Model : Crown 650SD
 Drive : Series 60

Auxiliary Brake : Band Brake
 Rated Power : 650

Mast

Mast Type : Telescoping Single
 Static Hook Load : 133,500 daN / 300,000 lbs
 Drill Line Size : 25

Mast Manufacturer : Rig Shop
 Mast Clear Height : 24 m / 80 ft
 Number of Lines : 8

Substructure

Substructure Type : Trailer Mounted Sub
 Floor Height : 4 m / 13 ft
 Rotary Capacity : 133500 daN / 300000 lbs

Substructure Manufacturer : Rig Shop
 Clear Height : 3.8 m / 12 ft
 Set Back Capacity :

Top Drive

Manufacturer / Model : FDS 150T
 Makeup Torque : 23000 Nm / 17100 ft-lb

Continuous Torque : 24000 Nm / 18000 ft-lb
 Breakout Torque : 25000 Nm / 19000 ft-lb

Hoisting and Rotating Equipment

Hook Capacity :
 Block Capacity : 133,500 daN / 300,000 lbs
 Rotary Table Model : End Drill System

Block Model : FDS 150T Split Block
 Swivel Capacity :
 Rotary Table Clearance : 445 mm / 17.5 in

Mud Pump 1

Manufacturer & Model : F1000
 Stroke : 254 mm / 10 in

Rated Power : 746 kW / 1000 hp
 Drive : Series 2000 c/w pacific rim

Mud Pump 2

Manufacturer & Model : F1000
 Stroke : 254 mm / 10 in

Rated Power : 746 kW / 1000 hp
 Drive : Series 2000 c/w pacific rim

Mud System

High Pressure Circulating System : 34000 kPa / 5000 psi
 # of Mud Tanks : 2
 Trip Tank Volume : 3.8 m3 / 1000 gal
 Shale Shaker Model : Derrick 503
 Additional Information : inlet 76mm, outlet 152 mm

Mud Tank Volume : 76 m3 / 20000 gal
 Second Mud Tank Volume : 22 m3 / 5800 gal
 # of Shale Shakers : 1
 Atmospheric Degasser : 762

Well Control System

Trim Type : NACE
 Accumulator Volume : 302 L / 80 gal
 Choke Manifold Size : 52

Acumulator Manufacturer : Control Technology
 Accumulator Pump : Triplex pump
 Choke Manifold Pressure Rating : 21000 kPa / 3000 psi

Power

Power Distribution Type : 350kw 480v/208v AC Diesel
 Generator Size 1 : 350

Generator Model 1 : Stamford

Miscellaneous Equipment

Boiler Rating : 80
 Fuel Tank Capacity : 18000 L / 4700 gal
 Water Tank Capacity : 40000 L / 10500 gal

of Fuel Tanks : 1
 # of Water Tanks : 1
 Tubulars : Rig carries sufficient tubular inventory of drill collars and drill pipe to drill 75% of rated depth capacity. Exact quantities and descriptions of tubulars available through Savanna Contracts Representative

Special Equipment : Range 3 HWDP available., Iron roughneck, hydraulic slips. Specific inventory subject to change. Contact sales representative.

Load List

Total Loads Summer : 18

Total Loads Winter : 19